

FEATURES 設備特性

1. Designed for high viscosity hot melt adhesives and large flow rate.
本機專為高黏度，大吐出量設計。
2. Constant glue flow by precise gear pump.
精密齒輪泵，出膠穩定，使用壽命長。
3. Teflon-coated tank for easy maintenance.
使用鐵氟龍熔膠槽，保養維護更容易。
4. Individual temperature control with PID controller for pre-heating, melting tank, hose and dispensing gun.
熔膠槽、保溫管、噴頭組獨立控溫。
5. Easy connection with robotic system and easy operation.
適合搭配各式機械手臂、容易作業，利於不同產業的塗佈應用。



SPECIFICATIONS 設備規格

SPEC 規格	UNIT 單位	HS2510	HS3510
Tank Capacity 膠槽容量	Liter	20	30
Max. Melting Rate 最高熔膠速率	Kg/HR	20	30
Max. Operation Temp. 最高操作溫度	°C	200	200
Max. Viscosity 最大使用黏稠度	CPS	100000	100000
Available Hose/Gun 保溫管/噴槍數目	Set	1	1
Max. Glue Flow Rate 最大出膠速率	g/MIN	500	500
Weight 重量	Kg	Approx. 160	Approx. 170
Dimensions (L x W x H) 尺寸 (長 x 寬 x 高)	mm	844 x 500 x 973	844 x 500 x 973
Machine Power Rate 主機功率	Watt	10120	11120
Power Requirement 電力需求		220V AC, 29.3A, 50/60Hz, 3Φ	220V AC, 33.9A, 50/60Hz, 3Φ

* The flow rate depends on the viscosity of hot melt adhesive. 實際出膠量會依熱熔膠的黏稠度改變

* Total power consumption and electricity requirement depends on the adapter demand. 總功率與電力需求會依配件需求變動

